

**KANNUR UNIVERSITY**  
(PLANNING AND DEVELOPMENT BRANCH)  
NOTICE INVITING RE-TENDERS

PLD/E1/PARKING SHED&SECURITY GUARD ROOM/Nileswaram Campus/NAAC/2021

16/12/2022

Sealed competitive Re-Tenders, superscribed as 'Furnishing the Room of Security Guard at Nileswaram Campus of Kannur University' are invited from registered competent Electrical Contractors/firms.

The Details are as follows.

Sl.No.	Name of Work	EMD	RE-TENDER FEE	Time for the completion of work	Last date and time of submission
1	2	3	4	5	6
1	Furnishing the Room of the Security Guard at Nileswaram Campus of Kannur University	₹3,440/-	₹590/- (GST18% included)	2 months from the date of Agreement	<u>20/12/2022</u> at 3 PM

1.Re-Tender Form can be downloaded from the Kannur University Website [www.kannuruniversity.ac.in](http://www.kannuruniversity.ac.in).

2.A sum of ₹590/- (GST 18% included) towards the cost of Re-Tender form and an amount of ₹3,440/- as EMD should be remitted separately by way of Demand Draft drawn in favour of Finance Officer, Kannur University, payable at SBI South Bazar Branch, Kannur or Kannur Branch of any other Nationalized or scheduled Bank.

3.The Tenderer should send along with the tender an initial agreement executed and signed in Kerala Stamp Paper of value ₹ 200/-.

4.The Tenderer shall have valid GST registration and shall furnish a copy of registration certificate along with the tender documents.

5.The successful Tenderer before signing the Agreement and within the period specified in the work order, shall deposit a sum equivalent to 5% of the value of the contract as Security Deposit.

6. The rate quoted should be inclusive of GST and all other charges if any. The base rate, GST charges and other charges if any should be furnished separately and nothing extra shall be admissible over and above the rate quoted.

7. Payment will be made through account and no advance payment will be sanctioned

8. Received tenders will be opened on 30/12/2022 at 3.30 PM.

The Details of work can be had from the Engineering wing of the University, Thavakkara,Kannur, on all working days up to 5 pm.

The Registrar, Kannur University, reserves the right to reject any of the Re-tenders or all the Re-tenders without assigning any reason whatsoever.

  
REGISTRAR(i/c)

To : 1.Notice Board  
2.Website  
3.EE

**TENDER SCHEDULE**

**Name of work :- Providing Toilet Facility In Security Cabin at Nileswaram Campus.**

SL. NO	QUANTITY	PARTICULARS	UNIT	RATE INCLUDING ALL TAXES		AMOUNT
				IN FIGURES (RS)	IN WORDS (RS)	
1	1.00	51.19.ST2 Supplying and installing ready made PVC Septic tank including the cost of carriage, trenching, placing at the level below ground level as specified as per the direction of engineer in charge (Provision forCC/RCC/Sand/06mm aggregate for the preparation of bed shall be paid separately) 2. 15 to below 25 flush capacity	each			
2	2.00	19.33 Constructing soak pit 1.20x1.20 m filled with brickbats including S.W. drain pipe 100 mm diameter and 1.20 m long complete-as per standard design.	each			
3	20.00	50.18.9.9.1 Providing and fixing PVC pipes including jointing of pipes with one step PVC solvent cement, trenching, refilling & testing of Joints complete as per direction of engineer in charge.110 mmdia 6kgf/cm2	metre			
4	4.00	50.18.9.22.4 Providing and fixing PVC moulded fittings/ accessories for Rigid PVC pipes, including jointing with PVC solvent cement- 110 mm dia Bend	nos			
5	1.26	4.1.4 Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level:1:2:4 }1 cement : 2 coarse sand : 4 graded stone aggregate 40 mm nominal size)	cum			
6	1.00	17.2.2 Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required:W.C. pan with ISI marked black solid plastic seat and lid	each			

7	1.00	50.17.1.5 Supplying and fixing CP Health Faucet superior quality ( Jagur or equivalent make ) including cost of materials and labour charges etc complete as per the direction of site Engineer-in-charge	nos			
8	2.00	18.53.1 Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS: 893115 mm nominal bore	each			
9	1.00	18.15.1 Providing and fixing brass bib cock of approved quality :15 mm nominal bore	each			
10	1.00	17.7.1 Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require:White Vitreous China Wash basin size 630x450 mm with a pair of 15 mm C.P. brass pillar taps	each			
11	5.80	9.119 Providing and fixing factory made P.V.C. door frame of size 50x47 mm with a wall thickness of 5 mm, made out of extruded 5 mm rigid PVC foam sheet, mitred at corners and joined with 2 Nos. of 150 mm long brackets of 15x15 mm M.S. square tube, the vertical door frame profiles to be reinforced with 19x19 mm M.S. square tube of 19 gauge, EPDM rubber gasket weather seal to be provided through out the frame. The door frame to be fixed to the wall using M.S. screws of 65/100 mm size, complete as per manufacturer's specification and direction of Engineer-in Charge	metre			

12	1.68	<p>9.120.2 Providing and fixing factory made panel PVC door shutter consisting of frame made out of M.S. tubes of 19 gauge thickness and sized of 19 mm x 19 mm for styles and 15x15 mm for top &amp; bottom rails. M.S. frame shall have a coat of steel primers of approved make and manufacture. M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5mm thick, 95 mm wide PVC sheet out of which 75 mm shall be tapered in 45 degree on th inner side to form top and bottom rail and 115 mm wide PVC sheet out of which 75 mm shall be flat and 20 mm shall be tapered on both sides to form lock rail. Top, bottom and lock rails shall be provided both side of the panel. 10 mm (5 mmx2) thick, 20 mm wide cross PVC sheet be provided as gap insert for top rail &amp; bottom rail. paneling of 5 mm thick both side PVC sheet to be fitted in the M.S. frame welded /sealed to the styles &amp; rails with 7 mm (5 mm + 2 mm ) thick x 15 mm wide PVC sheet beading on inner side, and joined together with solvent cement adhesive. An additional 5 mm thick PVC strip of 20 mm width is to be stuck on the interior side of the 'C' Channel using PVC solvent adhesive etc. complete as per direction of Engineer -in-charge, manufacture's specification &amp; drawing.30 mm thick pre laminated PVC door shutters</p>	sqm			
13	1.00	<p>9.106.1 Providing and fixing PTMT handles with necessary screws etc. complete.125x34x24 mm weighing not less than 23 gms</p>	nos			
14	1.00	<p>9.108.1 Providing and fixing PTMT Tower Bolts with 12 mm one piece rod inside and necessary screws etc., complete.152x42x18 mm weighing not less than 60 gms</p>	nos			
15	2.00	<p>50.9.15.1 Supplying and fixing 200 mm Aluminium aldrop</p>	nos			

16	5.01	<p>21.1.1.2 Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS : 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing /paneling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.(Glazing, paneling and dash fasteners to be paid for separately):For fixed portion Powder coated aluminium (minimum thickness of powder coating 50 micron)</p>	kg			
17	5.01	<p>21.1.2.2 For shutters of doors, windows &amp; ventilators including providing and fixing hinges / pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber/ neoprene gasket required (Fittings shall be paid for separately) Powder coated aluminium (minimum thickness of powder coating 50 micron)</p>	kg			
18	2.006 sqm	<p>21.3.1 Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of Engineer - in -Charge. ( Cost of aluminium snap beading shall be paid in basic item):With float glass panes of 4.0 mm thickness</p>	sqm			
19	25.00	<p>16.70.1 Providing and fixing G.I. chain link fabric fencing of required width in mesh size 50x50 mm including strengthening with 2 mm dia wire or nuts , bolts and washers as required complete as per the direction of Engineer-in- charge.Made of G.I. wire of dia 4 mm</p>	sqm			

20	24.00	<p>100.1.3 Excavating trenches of required width for pipes, cables, etc including excavation for sockets, and dressing of sides, ramming of bottoms, depth exceeding 3m in depth but not exceeding 4.5 m, including getting out the excavated soil, and then returning the soil as required, in layers not exceeding 20 cm in depth, including consolidating each deposited layer by ramming, watering, etc. and disposing of surplus excavated soil as directed, within a lead of 50 m : 3.0m to 4.50m All kinds of soil as directed, within a lead of 50 m : 3.0m to 4.50m All kinds of soil (Ref. Item No. 2.12 of DSR)</p>	cum			
Total						

\*Rate including GST

(Rupees.....Only)

Signature:

Name & Address of the Tenderer:

Date:

*Sd/-*  
Registrar