



KANNUR UNIVERSITY
കണ്ണൂർ സർവകലാശാല

PLANNING AND DEVELOPMENT BRANCH
(PLD E SECTION)

NOTICE INVITING RE-QUOTATIONS

PLD/E1/16075/2025

04.02.2026

Sealed competitive Quotations super scribed as "Water proofing above Lift rooms at Mangattuparamba, Dharmashala and Palayad Campuses of Kannur University" are invited from registered competent Contractors/firms.

Quotations with all details should reach the office of the Registrar, Kannur University, Kannur-2 on or before 19.02.2026 at 3.00 pm and the Quotations will be opened at 3.30 pm on the same day.

Conditions:

1. The rate quoted should be **inclusive of GST and all other charges if any**. The base rate, GST charges and other charges if any should be furnished separately and nothing extra shall be admissible over and above the rate quoted.
2. The Contractor shall arrange suitable materials and equipment and should be got approved by the Executive Engineer/ Assistant Executive Engineer of the University and work shall be executed as per KPWD specifications.
3. The Payment will be made through bank account and no advance payment will be sanctioned.
4. The successful bidder will be required to deposit Performance Guarantee/Security Deposit as per rules.
5. Work shall be completed within **1 Month** from the date of agreement.
6. A defect liability period is **1 year** from the date of completion of work.
7. Quotation forms and details of works can be had from the website www.kannuruniv.ac.in.
8. The Registrar, Kannur University reserves the right to reject any of the quotations or all the quotations without assigning any reason whatsoever.
9. Quotation schedule is appended herewith.

Sd/-

Registrar

To

1. Notice Board
2. Website



KANNUR UNIVERSITY

QUOTATION SCHEDULE

WATER PROOFING ABOVE LIFTROOM AT MANGATTUPARAMB, DHARMASHALA AND PALAYAD CAMPUS.

SL. NO	QTY	PARTICULARS	UNIT	RATE	AMOUNT (RS)
1	6.000	50.18.9.16.2 PVC pipes, fittings including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step PVC solvent cement and testing of joints complete as per direction of Engineer-in-Charge 50 mm dia 6Kgf/cm ² - External work - Exposed on wall	m		
2	38.250	14.90 .1 laying APP (Atactic Polypropylene Polymer) modifiedprefabricated five layer, 3 mm thick water proofing membrane, black finishedreinforced with glass fibre matt consisting of a coat of bitumen primer forbitumen membrane @ 0.40 litre/sqm by the same membrane manufactureddensity at 25 degreee, 0.87 - 0.89 kg/litre and viscocity 70 - 160 cps. Over the primercoat the layer of membrane shall be laid using butane torch and sealing alljoints etc., and preparing the surface complete. The vital physical and chemicalparameters of the membrane shall be as under : Joint strength in longitudinaldegree and transverse direction at 23degree as 350/300 N/5 cm. Tear strength in longitudinaland transverse direction as 60/80N. Softening point of membrane not less than150degree. Cold flexibility shall be upto -2 degree when tested in accordance with ASTM,D - 5147. The laying of membrane shall be got done through the authorisedapplicator of the manufacturer of membrane :3 mm thick	m ²		
3	6.000	od29985/2025_2026 : Labour	no		
		TOTAL			
		GST 18%			
		GRAND TOTAL			

(Rupees.....Only)

Signature:

Name & Adress of the Quotationer:

Date: