

  
KANNUR UNIVERSITY  
(Planning and Development Branch)  
NOTICE INVITING QUOTATIONS

PLD/E3/20267/2022

03.07.2023

Sealed competitive Quotations Superscribed as "Maintenance Work-Repairing Broken Glass-Indoor Stadium-Mangattuparamba Campus" are invited from registered competent Contractors/firms.

Quotations with all details should reach the office of the Registrar, Kannur University, Kannur -02 on or before 13/07/2023 at 3pm and the quotations will be opened at 3.30pm on the same day.

Conditions:

1. The rate quoted should be inclusive of GST and all other charges if any. The base rate, GST charges and other charges if any should be furnished separately and nothing extra shall be admissible over and above the rate quoted
2. The contractor shall arrange all material & equipment and should be got approved by the Executive Engineer and work shall be executed as per KPWD specifications.
3. Payment will be made through bank account and no advance payment will be sanctioned.
4. Work shall be completed within one month from the date of Agreement. Quotation forms and details of works can be had from the [www.kannuruniv.ac.in](http://www.kannuruniv.ac.in).

The Registrar, Kannur University reserves the right to reject any of the quotations or all the quotations without assigning any reason whatsoever.

  
REGISTRAR (i/c)

↓

KANNUR UNIVERSITY						
QUOTATION SCHEDULE						
Name of work: Maintenance work - Repairing broken glass, Indoor Stadium - Mangattuparamba Campus						
SL. NO	QTY	PARTICULARS	UNIT	RATE		AMOUNT (RS)
				IN FIGURES (RS)	IN WORDS (RS)	
1	10	9.106.1 Providing and fixing PTMT handles with necessary screws etc. complete.125x34x24 mm weighing not less than 23 gms	nos			
2	3	9.95.1 Providing and fixing ISI marked aluminium butt hinges anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with necessary screws etc. complete:125x75x4 mm	nos			
3	11	9.97.2 Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per : 1868), transparent or dyed to required colour or shade, with necessary screws complete:250x10 mm	nos			
4	5.67	9.120.2 Providing and fixing factory made panel PVC door shutter consisting of frame made out of M.S. tubes of 19 gauge thickness and sized of 19 mm x 19 mm for styles and 15x15 mm for top & bottom rails. M.S. frame shall have a coat'of steel primers of approved make and manufacture. M.S. frame covered with 5mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5mm thick, 95 mm wide PVC sheet out of which 75 mm shall be tapered in 45 degree on the inner side to form top and bottom rail and 115 mm wide PVC sheet out of which 75 mm shall be flat and 20 mm shall be tapered on both sides to form lock rail. Top, bottom and lock rails shall be provided both side of the panel. 10 mm (5mmx2) thick, 20 mm wide cross PVC sheet be provided as gap insert for top rail & bottom rail. paneling of 5 mm thick both side PVC sheet to be fitted in the M.S. frame welded /sealed to the styles & rails with 7mm (5 mm + 2 mm ) thick x 15 mm wide PVC sheet beading on inner side, and joined together withsolvent cement adhesive. An additional 5 mm thick PVC strip of 20 mm width is to be stuck on the interior side of the 'C' Channel using PVC	Sq m			
5	45.302	21.3.1 Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of Engineer -in - Charge. ( Cost of aluminium snap beading shall be paid in basic item):With float glass panes of 4.0mm thickness	Sq m			
6	1	9.83 Providing and fixing aluminium die cast body tubular type universal hydraulic door closer (having brand logo with ISI, IS : 3564, embossed on the body, door weight upto 35 kg and door width upto 700 mm), with necessary accessories and screws etc. complete	nos			
7	1.45	21.5 Providing and fixing powder coated aluminium work ( minimum thickness of powder coating 50 micron)consisting of tee /angle sections, of approved make conforming to IS : 733 in frames of false ceiling including aluminium angle cleats with necessary C.P brass/ stainless steel sunk screws, aluminium perimeter angles fixed to wall with stainless steel rawl plugs @ 450 mm centre to centre and fixing the frame work to G.I level adjusting hangers 6 mm dia. with necessary cadmium plated machine screws all complete as per approved architectural drawings and direction of the Engineer-in-Charge ( level adjusting hangers, ceiling cleats and expansion hold fasteners to be paid for separately ).	Kg			

8	10.4	9.119 Providing and fixing factory made P.V.C. door frame of size 50x47 mm with a wall thickness of 5 mm, made out of extruded 5 mm rigid PVC foam sheet, mitred at corners and joined with 2 Nos. of 150 mm long brackets of 15x15 mm M.S. square tube, the vertical door frame profiles to be reinforced with 19x19 mm M.S. square tube of 19 gauge, EPDM rubber gasket weather seal to be provided through out the frame. The door fame to be fixed to the wall using M.S. screws of 65/100 mm size, complete as per manufacturer's specification and direction of Engineer-in-Charge	metre			
9	1	od351121/2022_2023 Providing joint filling using plaster of Paris, silicone sealant using gun, including labour charge and providing border using mortar at window sill level, changing rubber beading, applying paint etc complete as per direction of department officers	each			
						TOTAL
						Add 18% GST
						Grand Total

(Rupees.....Only)

Signature:

Name & Address of the Quotationer:

Date: